

| | | | |
|------------------------------|-------------------------------------|---------------------------|-------------------------------------|
| PROJECT: TER-395-24.50 | DRILLING FIRM / OPERATOR: ODOT / A. | DRILL RIG: ACME DRILL RIG | STATION / OFFSET: 164+92:9.0 |
| TYPE: LANDSLIDE | SAMPLING FIRM / LOGGER: ODOT / B. | HAMMER: ACME HAMMER | ALIGNMENT: CL SR 395 |
| PID: 99999 BR ID: N/A | DRILLING METHOD: 3.25" HSA / NQ2 | CALIBRATION DATE: 2/20/07 | ELEVATION: 585.3 (MSL) |
| START: 12/9/08 END: 12/10/08 | SAMPLING METHOD: SPT / NQ2 | ENERGY RATIO (%): 81.9 | COORD: 6445586.000 N, 2055511.000 E |
| | | | EXPLORATION ID: B-002 |
| | | | PAGE: 1 of 1 |

| MATERIAL DESCRIPTION AND NOTES | ELEV. | DEPTH | SPT/RQD | N60 | REC (%) | SAMPLE ID | HP (tsf) | GRADATION (%) | | | | | ATTERBERG | | | WC | ODOT CLASS (GI) | BACK FILL |
|--|-------|-------|---------|-----|---------|-----------|----------|---------------|----|----|----|----|-----------|----|----|----|-----------------|-----------|
| | | | | | | | | GR | CS | FS | SI | CL | LL | PL | PI | | | |
| ASPHALT (18") OVER CONCRETE (9") | | 0 | | | | | | | | | | | | | | | | |
| | | 1 | | | | | | | | | | | | | | | | |
| | | 2 | | | | | | | | | | | | | | | | |
| | 583.1 | | | | | | | | | | | | | | | | | |
| MEDIUM DENSE, BROWN, GRAVEL, "AND" TO SOME SAND, TRACE SILT, TRACE CLAY, MOIST | | 4 | | | | | | | | | | | | | | | | |
| | | 3 | | | | | | | | | | | | | | | | |
| | | 5 | 5 | 14 | 78 | SS-1 | - | 53 | 20 | 16 | 7 | 4 | NP | NP | NP | 10 | A-1-a (0) | |
| | | 4 | 5 | | | | | | | | | | | | | | | |
| | | 7 | 5 | 15 | 89 | SS-2 | - | 51 | 21 | 13 | 8 | 7 | NP | NP | NP | 10 | A-1-a (0) | |
| | | 5 | | | | | | | | | | | | | | | | |
| | 579.8 | | | | | | | | | | | | | | | | | |
| STIFF TO VERY STIFF, REDDISH BROWN, SILTY CLAY, SOME GRAVEL, LITTLE SAND, MOIST | | 2 | | | | | | | | | | | | | | | | |
| | | 6 | | | | | | | | | | | | | | | | |
| | | 3 | 3 | 8 | 89 | SS-3 | 1.25 | 35 | 6 | 7 | 19 | 33 | 39 | 17 | 22 | 21 | A-6b (8) | |
| | | 7 | 3 | | | | | | | | | | | | | | | |
| | | 4 | 3 | 11 | 72 | SS-4 | 1.5 | 32 | 9 | 8 | 18 | 33 | 39 | 18 | 21 | 20 | A-6b (7) | |
| | | 8 | | | | | | | | | | | | | | | | |
| | | 4 | 2 | | | | | | | | | | | | | | | |
| | | 9 | | | | | | | | | | | | | | | | |
| | | 5 | 2 | 16 | 89 | SS-5 | 1.75 | - | - | - | - | - | - | - | - | - | 18 | A-6b (V) |
| | | 10 | | | | | | | | | | | | | | | | |
| | | 7 | 5 | | | | | | | | | | | | | | | |
| | | 7 | 5 | 20 | 72 | SS-6 | 2.25 | - | - | - | - | - | - | - | - | - | 19 | A-6b (V) |
| | | 11 | | | | | | | | | | | | | | | | |
| | | 8 | | | | | | | | | | | | | | | | |
| | 573.3 | | | | | | | | | | | | | | | | | |
| SS-7 PUSHING COBBLE LAST 6" | | 12 | 5 | | | | | | | | | | | | | | | |
| | | 7 | 5 | 45 | 78 | SS-7 | 4.0 | 24 | 6 | 14 | 25 | 31 | 36 | 19 | 17 | 18 | A-6b (7) | |
| | | 13 | | | | | | | | | | | | | | | | |
| | | 26 | | | | | | | | | | | | | | | | |
| NONE | | | | | | | | | | | | | | | | | | |
| ABANDONMENT METHODS, MATERIALS, QUANTITIES: PUMPED 20 LB. BENTONITE POWDER; 4 BAGS CEMENT; 25 GAL. WATER | | | | | | | | | | | | | | | | | | |